

§ 428.112

401 of this chapter shall apply to this subpart.

(b) The term “raw material” shall mean all latex solids used in the manufacture of latex foam.

§ 428.112 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

| Effluent characteristic | Effluent limitations | |
|---|-----------------------|---|
| | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kg of raw material) | | |
| Zinc | 0.058 | 0.024 |
| BOD ₅ | 2.4 | 1.4 |
| TSS | 2.26 | 0.94 |
| pH | (¹) | (¹) |
| English units (lb/1,000 lb of raw material) | | |
| Zinc | 0.058 | 0.024 |
| BOD ₅ | 2.4 | 1.4 |
| TSS | 2.26 | 0.94 |
| pH | (¹) | (¹) |

¹ Within the range 6.0 to 9.0.

[40 FR 2345, Jan. 10, 1975, as amended at 60 FR 33964, June 29, 1995]

§ 428.113 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a point source subject to the provisions of this subpart after application of the best available technology economically achievable:

40 CFR Ch. I (7–1–07 Edition)

| Effluent characteristic | Effluent limitations | |
|---|-----------------------|---|
| | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kg of raw material) | | |
| Zinc | 0.058 | 0.024 |
| BOD ₅ | 2.4 | 1.4 |
| TSS | 2.26 | 0.94 |
| pH | (¹) | (¹) |
| English units (lb/1,000 lb of raw material) | | |
| Zinc | 0.058 | 0.024 |
| BOD ₅ | 2.4 | 1.4 |
| TSS | 2.26 | 0.94 |
| pH | (¹) | (¹) |

¹ Within the range 6.0 to 9.0.

§ 428.114 [Reserved]

§ 428.115 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

| Effluent characteristic | Effluent limitations | |
|---|-----------------------|---|
| | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kg of raw material) | | |
| Zinc | 0.058 | 0.024 |
| BOD ₅ | 2.4 | 1.4 |
| TSS | 2.26 | 0.94 |
| pH | (¹) | (¹) |
| English units (lb/1,000 lb of raw material) | | |
| Zinc | 0.058 | 0.024 |
| BOD ₅ | 2.4 | 1.4 |
| TSS | 2.26 | 0.94 |
| pH | (¹) | (¹) |

¹ Within the range 6.0 to 9.0.

§ 428.116 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or

Environmental Protection Agency

Pt. 429

pollutant properties, controlled by this section, which may be discharged to a publicly owned treatment works by a new point source subject to the provisions of this subpart:

| Pollutant or pollutant property | Pretreatment standards | |
|---|------------------------|---|
| | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kkg of raw material) | | |
| Zinc | 0.058 | 0.024 |
| BOD ₅ | (¹) | (¹) |
| TSS | (¹) | (¹) |
| pH | (¹) | (¹) |
| English units (lb/1,000 lb of raw material) | | |
| Zinc | 0.058 | 0.024 |
| BOD ₅ | (¹) | (¹) |
| TSS | (¹) | (¹) |
| pH | (¹) | (¹) |

¹ No limitation.

[40 FR 2345, Jan. 10, 1975, as amended at 60 FR 33964, June 29, 1995]

PART 429—TIMBER PRODUCTS PROCESSING POINT SOURCE CATEGORY

GENERAL PROVISIONS

Sec.

429.10 Applicability.

429.11 General definitions.

429.12 Monitoring requirements. [Reserved]

Subpart A—Barking Subcategory

429.20 Applicability; description of the barking subcategory.

429.21 Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).

429.22 Effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT). [Reserved]

429.23 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT). [Reserved]

429.24 New source performance standards (NSPS).

429.25 Pretreatment standards for existing sources (PSES).

429.26 Pretreatment standards for new sources (PSNS).

Subpart B—Veneer Subcategory

429.30 Applicability; description of the veneer subcategory.

429.31 Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).

429.32 Effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT). [Reserved]

429.33 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).

429.34 New source performance standards (NSPS).

429.35 Pretreatment standards for existing sources (PSES).

429.36 Pretreatment standards for new sources (PSNS).

Subpart C—Plywood Subcategory

429.40 Applicability; description of the plywood subcategory.

429.41 Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).

429.42 Effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT). [Reserved]

429.43 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).

429.44 New source performance standards (NSPS).

429.45 Pretreatment standards for existing sources (PSES).

429.46 Pretreatment standards for new sources (PSNS).

Subpart D—Dry Process Hardboard Subcategory

429.50 Applicability; description of the dry process hardboard subcategory.

429.51 Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).

429.52 Effluent limitations representing the degree of effluent reduction attainable